MULLANEY SUPPLY CO.

MATERIAL SAFETY DATA

1. PRODUCT IDENTIFICATION

PRODUCT NAME:

PINPOINT

SYNONYMS:

Anionic Polyacrylamide in water-in-oil Emulsion

CHEMICAL FAMILY:

Polyacrylamide

GENERIC DESCRIPTION:

2. HAZARDOUS INGREDIENTS

OSHA REGULATED COMPONENTS COMPONENT

CAS. NO.

WT % (OPT.)

EXPOSURE LIMITS

PETROLEUM DISTILLATE

Proprietary

3. EFFECTS OF OVEREXPOSURE:

May cause eye irritation.

SKIN: INHALATION: Causes skin irritation.

ORAL:

Material is not expected to be harmful if inhaled. If inhaled, move to fresh air.

If swallowed, call a physician. Seek medical help. Do not induce vomiting.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon a compositions, component data and / or expert review of the product. Overexposure to any chemical may result in enhancement of pre-existing adverse medical condition and allergic reaction.

4. EMERGENCY FIRST AID

EYES: SKIN:

Flush immediately with water for 15 minutes. Obtain medical attention without delay. Remove contaminated clothing. Without delay, wash skin with soap and water. Launder

contaminated clothes.

INHALATION:

Material is not expected to be harmful if inhaled. If inhaled, remove to fresh air.

INGESTION:

If ingested, seek medical help. Do not induce vomiting.

5. REACTIVITY DATA

STABILITY:

Stable.

CONDITIONS TO AVOID:

None known.

POLYMERIZATION:

Will not occur.

INCOMPATIBILITY:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition or combustion may produce carbon monoxide, carbon

dioxide, ammonia, hydrogen chloride and/or oxides of N.

6. PHYSICAL PROPERTIES

APPEARANCE AND ODOR:

Grayish White Milky Liquid; Faint ammonia odor ~212° F

BOILING POINT:

Not available

MELTING POINT: VAPOR PRESSURE (mmg of Hg):

Not determined

SPECIFIC GRAVITY:

1.0 (+/-.05)

VAPOR DENSITY (AIR=1):

Similar to water

% VOLATILE (BY WT.): EVAPORATION RATE (Ether=1): 65% Not available

SOLUBILITY IN WATER:

Limited by viscosity

7. NFPA HAZARD RATING (National Fire Protection Association)

Special

FIRF:

Materials that must be preheated before ignition can

occur.

Health 2

0 Reactivity

HEALTH:

Materials which on intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical treatment is

given.

REACTIVITY:

Materials which in themselves are normally stable, even under fire exposure conditions, and which are

not reactive with water.

8. FIRE AND EXPLOSION HAZARD INFORMATION

FLASHPOINT:

>200°F (Pensky-Martens closed cup ASTM D93) Not available.

FLAMMABLE LIMITS: **EXTINGUISHING MEDIA:**

FIRE FIGHTING:

Water Spray, Dry Chemical, and CO2

Use water to keep containers cool. Use universal-type foams on larger fires. Smaller fires should be extinguished with carbon dioxide or dry

chemical. Do not use water or foam directly on the fire. Use selfcontained breathing apparatus with fighting any fire in an enclosed area.

UNUSUAL FIRE HAZARD: None known.

9. SPECIAL PRECAUTIONS

HANDLING AND STORAGE:

Avoid contact with eyes, skin and clothing. Store in cool dry place. Keep in original container tightly closed. Do not reuse empty container. To avoid product degradation and equipment corrosion, do not use iron, copper or aluminum containers or equipment.

OTHER PRECAUTIONS:

Keep out of reach of children. Spilled material becomes very slippery

when wet.

10. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

VENTILATION:

PROTECTIVE GLOVES:

EYE PROTECTION:

OTHER PROTECTION:

None required for normal use.
Normal room ventilation (mechanical) should be satisfactory.

PVC-coated.

Wear goggles or a face shield.

Wear goggles or safety glasses for operations where eye or face contact

can occur.

11. SPILL OR LEAK PROCEDURES

SPILLS OR RELEASES:

Where exposure levels are not known, wear NIOSH approved, positive pressure, self-contained respirator. Wear impervious boots.

CAUTION: Spilled material becomes very slippery when wet. Spilled material should be absorbed onto an inert material and scooped up. The area should be thoroughly flushed with water. If slipperiness remains,

apply more dry-sweeping compound.

WASTE DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Dispose of in an approved waste disposal facility in accordance with all Federal,

State and Local Regulations.

CONTAINER DISPOSAL:

Triple rinse (or equivalent) adding rinse water to application tank. Offer container for recycling or dispose of in a sanitary landfill or by other procedures approved by local regulations.

Page 3 of 3 Date of Issue 10-16-00 Date of Revision: 06-30-03

12. TOXICOLOGICAL INFORMATION

Toxicological information for the product is found under Section 2. HAZARDOUS INGREDIENTS. Toxicological information on the OSHA regulated components of this product is as follows:

Petroleum distillate has acute oral (rat) and dermal (rabbit) LD50 values of >5000 mg/kg and >3000 mg/kg, respectively. Prolonged or repeated skin contact tends to remove skin oils, possibly leading to irritation and dermatitis. Direct contact may cause eye irritation. Overexposure to high vapor concentrations, >~700 ppm, are irritating to the eyes and respiratory tract and may cause headaches, dizziness, drowsiness, and other central nervous system effects, including death. Aspiration of minute amounts during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

California Proposition 65 Warning (applicable in California only) – This product contains (a) chemical(s) known to the State of California to cause cancer.

13. REGULATORY INFORMATION

COMPOUNDS WHICH REQUIRE REPORTING UNDER SARA TITLE III

Sara regulated compound % Wt.

CAS NO.

No compounds present in quantities which are regulated.

The recommendation for safe handling and protection procedures is believed to be generally suitable for the standard uses of this compound. However, each user should identify his intended uses of this material and determine whether they are appropriate. All data included in this document is released as typical values and should not be utilized to determine the suitability of this material for a particular use or purpose. No warranty, either expressed or implied, is hereby made, nor do we give permission, inducement, or recommendations to practice any patented invention without a license. All data is offered for consideration, investigation and verification purposes only.

MULLANEY SUPPLY CO.

5552 Smoker Road, Centerville, IN 47330